

✓
L2 ANSWER 203 OF 259 CA COPYRIGHT 2005 ACS on STN
AN 101:136487 CA
ED Entered STN: 13 Oct 1984
FI Aerobic stabilization of organic sludges
IN Apro, Istvan; Benedek, Pal; Czepek, Gyula; Farkas, Peter; Mucsy, Gyorgy;
Olah, Jozsef; Torocsik, Ferenc
PA Vizgazdalkodasi Tudomanyos Kutato Kozpont, Hung.; Keletmagyarorszagi
Vizugyi Tervezo Vallalat
SO Hung. Teljes, 7 pp.
CODEN: HUXXB
DT Patent
LA Hungarian
IC C02F003-12; C02F011-00
CC 60-5 (Waste Treatment and Disposal)
FAN.CNT 1

	PATENT NO.	KIND	DATE	APPLICATION NO.	DATE
PI	HU 31027	O	19840428	HU 1982-606	19820301
	HU 188572	B	19860428		
PRAI	HU 1982-606		19820301		

CLASS
PATENT NO. CLASS PATENT FAMILY CLASSIFICATION CODES

HU 31027 IC C02F003-12IC C02F011-00

AB Sludge is aerated in an aeration basin for 8-12 days using a conventional aeration unit. The sludge is dewatered after mixing with perlite or fly ash. Metal salts with valencies 2 and 3 (e.g., Fe²⁺, Ca²⁺, Al³⁺) are added and the pH is adjusted to 8.3-8.5 with lime. Washing water of equal or larger volume of the sludge is added and the treated sludge is thickened. Part of the thickened sludge is recirculated to the aeration basin and the remainder of the sludge is dewatered. The decanted sludge water is introduced into an activated-sludge basin.

ST aerobic stabilization org sludge

IT Perlite

RL: PROC (Process)

(additive, in wastewater organic sludge dewaterin

teach dewatering sludge
with fly ash